

SWING X RANGE

3HD, 4HD & 5LH - 230V Swing Gate Operators

GLOBAL
ACCESS

For Gates
up to 500KG



tousek



Made in
AUSTRIA



TOUSEK SAFE LOCK

Enhance your experience with the Swing X range by adding a Safe Lock to your installation. Features include:

- Motorised in both directions; easy to operate
- Increases gate security
- Protects operator against wind or vandal force
- 125mm travel; suited to most applications
- Vertical and horizontal mounting options/ easy to install

Single Kit: #1045-0037 Double Kit: #1045-0038



Suitable to residential, commercial and condominium



Self-locking motor spindle



Euro-key emergency manual release



Machine cut, hardened steel gears



Adjustable soft stop, both open and close




Separate control board with readable LCD Display




Built In stops no need to purchase additional



Intelligent Motor with encoder eliminating limit switches



Robust motor-gear unit



Integrated limit switches



A torque sensor activates the automatic reverse system (ARS), causing the operator to stop and reverse upon contact with an obstacle, ensuring high safety.

ARS (Automatic Reverse)

Optional Bolt-On Brackets (Sold Separately)



Reduce Welding Requirements

Post Bolt Bracket - Zinc	#6049-0561
Post Bolt Bracket - Stainless Steel	#6049-0610
Gate Bolt Bracket - Zinc	#6049-0562

	Motor Power	Max Gate Leaf	Max Gate Weight	Max Stroke	Min Side Room	Travel Speed sec	Single Kit Part Number	Double Kit Part Number
X 3HD	230V	3m	500kg	320mm	200-260 mm	23	1616-0032	1616-0031
X 4HD		4m		320mm		29	1616-0034	1616-0035
X 5LH		5m		450mm		41	1616-0028	1616-0029

POPULAR ACCESSORIES

E-Lock/Magnet Module	Magnet output for open and closed positions	#1018-0088
Courtyard Lamp/Control Lamp Module	For 230V lamp connection, Max. 100W	#1044-0014
External Gate Status Module	Potential free signal contacts, Max. 24V, 10W	#1018-0087



1300 366 046



sales@global-access.com.au

For more information, visit our website!

global-access.com.au

